AD703627

TECHNICAL REPORT 13

TABLES OF DRIFT VELOCITIES OF SLOW ELECTRONS IN HELIUM, NEON, ARGON, KRYPTON, XENON, HYDROGEN, DEUTERIUM, NITROGEN, CARBON MONOXIDE, CARBON DIOXIDE, WATER VAPOR, NITROUS OXIDE, AND AMMONIA*

J. L. PACK
R. E. VOSHALL
A. V. PHELPS

ARPA Order Number: 125-61 (Amd. 4)

Contract Number: NONR 2584(00)

Project Code: 7200

Principal Investigators: A. V. Phelps
G. J. Schulz

D D C
APR 8 1970
B

Physics Department
Westinghouse Research Laboratories
Pittsburgh 35, Pennsylvania

*This research is a part of Project DEFENDER, sponsored by the Advanced Research Projects Agency, Department of Defense.

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield Va. 22151

This document has been approved for public release and sale; its distribution is unlimited.

25

Research Report 62-928-113-R1 July 23, 1962

TABLES OF DRIFT VELOCITIES OF SLOW ELECTRONS IN HELIUM, NEON, ARGON, KRYPTON, XENON, HYDROGEN, DEUTERIUM, NITROGEN, CARBON MONOXIDE, CARBON DIOXIDE, WATER VAPOR, NITROUS OXIDE, AND AMMONIA*

J. L. Pack
R. E. Voshall
A. V. Phelps
Physics Department

Westinghouse Research Laboratories
Beulah Road, Churchill Borough
Pittsburgh 35, Pennsylvania

---

*This research is a part of Project DEFENDER, sponsored by the Advanced Research Projects Agency, Department of Defense.

Research Report 62-928-113-R1

July 23, 1962

Tables of Drift Velocities of Slow Electrons in Helium, Neon, Argon, Krypton, Xenon, Hydrogen, Deuterium, Nitrogen, Carbon Monoxide, Carbon Dioxide, Water Vapor, Nitrous Oxide, and Ammonia*

J. L. Pack, R. E. Voshall, and A. V. Phelps
Westinghouse Research Laboratories, Pittsburgh 35, Pennsylvania

ABSTRACT

This raport presents in tabulated form the drift velocities of electrons in various gases. The drift velocities were measured in helium, neon, argon, krypton, xenon, hydrogen, deuterium, nitrogen, carbon monoxide, carbon dioxide, water vapor, nitrous oxide, and ammonia for E/p values from 10^{-4} to 30 volts/cm-mm Hg at several gas temperatures between 77°K and 443°K. In all gases except neon measurements were extended to low enough E/p such that the electrons were in thermal equilibrium with the gas.

*This work was supported by the Advanced Research Projects Agency through the Office of Naval Research.

I. EXPLANATION OF TABLES

This paper reports in tabulated form the measurements of drift velocities of electrons in helium, neon, argon, krypton, xenon, hydrogen, deuterium, nitrogen, carbon monoxide, carbon dioxide, water vapor, nitrous oxide, and ammonia. Discussions of the experimental technique, graphs of the data, and a partial analysis of the data are contained in previous papers.[1,2]

The following notation is used:[1]

$W_e(T)$ = drift velocity in centimeters per sec (cm/sec) at temperature T

Drift Distances = distance from the cathode to grid number 1 and from the cathode to grid number 2.

The values of E/p_{300} are expressed in units of volt/cm-mm Hg for an equivalent density at 300°K, i.e., $E/p_{300} = (E/N)\ 3.22 \times 10^{16}$ for all data given in this paper. Here N is the gas density. The normalized pressures, p_{300}, are the values measured using the manometer system and multiplied by 300/T. Here T is the temperature of the gas in the mobility tube.

The bias and rejection methods of obtaining the data are discussed under the "Conventional Grid Operation" and "Zero-Bias

1. J. L. Pack and A. V. Phelps, Phys. Rev. 121, 798 (1961).
2. J. L. Pack, R. E. Voshall, and A. V. Phelps, Phys. Res. 127, 2084 (1962).

Operation" sections of reference 1. Data were often taken at different pressures at constant E/p_{300} and a constant temperature thus giving a check on the measurements. The drift velocities are independent of pressure at a fixed E/p_{300} and temperature within the scatter of the data.

In helium, data were taken at two sets of drift distances and were consistent with each other. In all other gases data were taken at one set of drift distances. The data obtained by the bias method were identical to those obtained by the rejection method, except where excessive bias voltages were required to cut off the grids. In these cases and in the later gases studied the rejection method was used. Values are reported only if drift velocities calculated for the two drift distances agree within 10 percent. Exception to this are argon for $E/p_{300} < 0.0015$ where the difference was as large as 35 percent. In these cases the drift velocity was taken as the difference in the distances divided by the difference in transit times. Note that analysis of the neon data for $E/p_{300} < 10^{-2}$ by L. S. Frost and A. V. Phelps (private communication) shows that the data at 77°K and 300°K lead to apparent momentum transfer cross sections differing by as much as 30 percent and suggest errors in one or both sets of drift velocity data of as much as 10 percent.

The estimated uncertainties in voltage and pressure are discussed in reference 1. The distances between the grid wire mounts were measured to 1 percent. Warpage of the individual grid wires was less than ± 5 percent of the distance to the nearest grid or cathode.

II. TABLES

Table I - He

Drift velocity of electrons in helium
Drift distances = 1" and 2"

E/p_{300} (volts/cm-mm Hg)	W_e (77°K) (cm/sec)	p_{300} (mm-Hg)	W_e (195°K) (cm/sec)	p_{300} (mm-Hg)	W_e (300°K) (cm/sec)	p_{300} (mm-Hg)
1.0					9.65×10^5	9.86
0.5					6.44×10^5	9.86
0.4					5.6×10^5	97.3
0.2	3.8×10^5*	144			4.0×10^5	10.0
"					5.7×10^5	10.0
0.15					3.22×10^5	407.9
0.10	2.82×10^5*	144			2.62×10^5	98
"	2.83×10^5	555			2.60×10^5*	98
"					2.69×10^5	693
0.05	2.09×10^5*	144	1.95×10^5	965	1.87×10^5	98
"					1.85×10^5*	98
0.04					1.67×10^5	405.7
0.0333					1.51×10^5	693
0.025			1.345×10^5	965		
"			1.39×10^5	970		
0.02	1.27×10^5*	144			1.08×10^5	405.7
0.01	8.75×10^4*	144	7.5×10^4	970	6.43×10^4*	98
"	8.60×10^4	555			6.70×10^4	693
"	8.80×10^4*	956				
0.007					5.0×10^4	405.7
0.006	6.5×10^4	1238				
0.005	5.81×10^4*	144	4.38×10^4	970	3.54×10^4*	98
"	5.60×10^4*	956			3.68×10^4	693
0.003	3.98×10^4	555			2.36×10^4	405.9
"					2.32×10^4	689
0.002	2.80×10^4*	956	1.36×10^4	970	1.575×10^4	689
0.0015	2.23×10^4	1238			1.18×10^4	405.7
0.0014					1.10×10^4	689
0.001	1.55×10^4	952	1.015×10^4	970	7.95×10^3	689
"	1.51×10^4*	956				
0.0009	1.37×10^4	555				
0.0003	1.24×10^4	1238				
0.00075					5.77×10^3	405.7
0.0007					5.70×10^3	689
0.0005	8×10^3	952	5.08×10^3	970	4.31×10^3*	689
"					4.50×10^3	689
"					4.10×10^3	689
0.0004	6.53×10^3	1238			3.44×10^3	689
0.000257					2.12×10^3	689
0.00025			2.65×10^3	965		

*Denotes bias method - all others by rejection method.

Table I - He
(cont.)

E/P_{300} (volts/cm-mm Hg)	W_e (77°K) (cm/sec)	P_{300} (mm-Hg)	W_e (195°K) (cm/sec)	P_{300} (mm-Hg)	W_e (300°K) (cm/sec)	P_{300} (mm-Hg)
0.0002	3.22×10^3	1238				
0.0001	1.69×10^3	1238				
Drift distances - 2" and 4"						
1.0					9.55×10^5	8.40
0.3					5.40×10^5	8.40
0.222					4.20×10^5	94.1
0.100					2.80×10^5	94.1
0.03					1.425×10^5	94.1
0.01					6.88×10^4 to 6.60×10^4	94.1
0.003					2.36×10^4	94.1
0.001					7.95×10^3	544
0.0005					4.20 to 4.42×10^3	544

Table II - Ne

Drift velocity of electrons in Neon
Drift distances = 1" and 2"

E/p_{300} (volts/cm-mm Hg)	W_e (77°K) (cm/sec)	p_{300} (mm-Hg)	W_e (300°K) (cm/sec)	p_{300} (mm-Hg)
1.0			1.64×10^6*	18.
0.5			7.9×10^5*	48.35
0.20			4.94×10^5*	"
"			4.50×10^5*	291
0.129			3.90×10^5	466
0.108	3.63×10^5	545		
0.10			3.60×10^5*	48.35
"			3.30×10^5*	291
0.05	2.55×10^5	905	2.80×10^5*	48.35
"			2.54×10^5*	291
0.03			2.10×10^5	662
0.02	1.81×10^5	905	1.70×10^5	466
"			1.72×10^5*	291
0.01	1.33×10^5	545	1.27×10^5*	291
"			1.30×10^5	662
0.008	1.25×10^5	905		
0.006			1.00×10^5*	466
"			1.03×10^5	"
0.005			1.0×10^5	291
"			1.0×10^5	662
0.004	9.80×10^4	905		
0.003	8.83×10^4	545		
0.0024			7.1×10^4*	446
0.002			6.53×10^4	662
"			6.87×10^4	291
0.0015	6.53×10^4	905		
0.0013	6.05×10^4	905		
0.0012			5.4×10^4	466
0.001			5.24×10^4	291
"			4.96×10^4	654
0.00069			3.55×10^4	654
0.00065	4.84×10^4	905		
0.0006			3.74×10^4	466
0.0005			3.40×10^4	291
"			3.0×10^4	654
0.00043	3.63×10^4	905		
0.000425			3.17×10^4	466
0.00036			2.54×10^4	654

* Denotes Bias method used - all others by rejection method.

Table III

Drift velocity of electrons in Argon
Drift distances = 1" and 2"

E/p_{300} (volt/cm-mm Hg)	$W_e(77^oK)$ (cm/sec)	P_{300} (mm Hg)	$W_e(300^oK)$ (cm/sec)	P_{300} (mm Hg)
0.485			3.22×10^5	151.5
0.395			3.07×10^5	"
0.300			3.00×10^5	"
0.250			2.90×10^5	"
0.20			2.60×10^5*	297
0.12			2.36×10^5	151.5
0.10			2.27×10^5*	297
"			2.24×10^5*	462
0.0804			2.13×10^5	735
0.080	2.16×10^5*	740		
0.076	2.09×10^5*	780		
0.060			2.10×10^5	151.5
0.050			1.94×10^5*	297
"			1.88×10^5*	462
0.030			1.78×10^5	151.5
0.020	1.52×10^5*	780	1.54×10^5*	297
"			1.50×10^5	462
0.018	1.50×10^5	722		
0.0154			1.39×10^5*	735
0.01			1.30×10^5	297
"			1.34×10^5*	297
"			1.27×10^5	462
0.0076			1.16×10^5*	735
0.0062	1.13×10^5	710		
0.0050	1.10×10^5*	780	1.22×10^5	297
"			1.10×10^5	462
"			1.08×10^5*	"
0.00353			1.01×10^5*	735
0.0030	9.8×10^4	735		
0.002	9.25×10^4*	780	9.40×10^4	462
"			9.60×10^4*	462
0.00154			8.45×10^4	735
0.0015	6.12×10^4	735		
"	6.90×10^4*	780		
0.0010	2.67×10^4*	780	5.90×10^4	462
"	2.20×10^4*	735	6.20×10^4*	462
0.0008	1.59×10^4*	746		
0.00078	1.68×10^4*	746		
0.00077			4.60×10^4*	735
0.0005	9.4×10^3*	735	2.16 to	
"	9.8×10^3*	746	2.42×10^4*	735
0.00036			1.61×10^4*	735
0.0003	5.25×10^3*	746		
0.00026	5.0×10^3*	735		
0.00025	4.45×10^3*	735		
0.00020	3.54×10^3*	746	8.3×10^3*	735
			8.9×10^3*	735

* = bias method, all others by rejection method.

Table IV - Kr

Drift velocity of electrons in Krypton
Drift distances = 2" and 4"

E/p_{300} (volts/cm-mm Hg)	W_e (195°K) (cm/sec) all at p_{300}=885 mm Hg	W_e (300°K) (cm/sec)	p_{300} (mm-Hg)	W_e (368°K) (cm/sec)	p_{300} (mm-Hg)
1.00		3.14×10^5	15.36		
0.80		2.49×10^5	31.69		
0.596		2.42×10^5	31.69		
0.500		2.26×10^5	61.20		
0.300		2.02×10^5	61.20		
0.392		1.89×10^5	155.2		
0.200		1.77 "	155.2		
0.100		1.55 "	405.3		
0.05		1.35	405.3		
0.03	1.275×10^5				
0.025		1.25 "	405.3		
0.015	1.17 "	1.19 "	407		
0.010	1.00×10^5	9.95×10^4	405.3		
"		1.035×10^5	757.3		
0.009		1.00×10^5	407		
0.008	7.95×10^4	9.03×10^4	407		
"		8.45×10^4	757.3		
0.007		6.32×10^4	408		
0.006	4.02×10^4	5.14×10^4	757.3		
0.00558		4.25×10^4	405.3		
0.005		3.29×10^4	408		
0.004	1.612×10^4	2.12×10^4	408		
"		2.24×10^4	757.3		
0.003	1.09×10^4	1.332×10^4	408		
0.0025		1.07×10^4	757.3		
0.002	7.14×10^3	8.75×10^3	405.3	9.27×10^3	687
0.0015	5.35×10^3	6.12×10^3	757.3		
0.001	3.62×10^3	4.01×10^3	405.3	4.4×10^3	687
0.0007				3.12×10^3	687
0.0006		2.35×10^3	757.3		
0.0005	1.745×10^3	2.12×10^3	407	2.15×10^3	687
0.0004		1.576×10^3	757.3		
0.0003		1.30×10^3	757.3		
0.00026		1.096×10^3	757.3		

Table V - Xe

Drift velocity of electrons in Xenon
Drift distances - 2" and 4"

E/p_{300} (volts/cm-mm Hg)	W_e (195°K) (cm/sec)	p_{300} (mm-Hg)	W_e (300°K) (cm/sec)	p_{300} (mm-Hg)
1.0			1.78×10^5	20.36
0.70			1.57 "	39.30
0.594			1.53 "	"
0.50			1.56 "	"
"			1.42 "	79.3
0.40			1.44 "	39.3
0.30			1.29 "	79.3
"			1.27 "	149.6
0.20			1.215 "	79.3
"			1.22 "	149.6
0.15			1.09 "	299.1
0.125			1.11 "	79.3
0.10			1.04 "	149.6
0.08			9.9×10^4	299.1
0.07			9.82 "	149.6
0.06			9.64 "	299.1
0.05			9.75 "	149.6
0.04			8.87 "	299.1
0.035			8.50 "	721.9
0.03			8.08 "	299.1
0.025	7.31×10^4	831	7.48 "	299.1
0.0225			7.16 "	721.9
0.020	5.77×10^4	832	6.51 "	299.1
0.018			5.77 "	721.9
0.016			4.84×10^4	730
0.015	3.015×10^4	832		
"	2.82×10^4	562		
0.014			3.72×10^4	299.1
"			3.79 "	730
0.0125	1.855×10^4	562		
"	1.815 "	833		
0.012			2.34×10^4	299.1
"			2.54×10^4	482
"			2.65 x "	730
0.010	1.19×10^4	571	1.42×10^4	149.6
"	1.13×10^4	833	1.67×10^4	482.7
"			1.775×10^4	730
0.009			1.284×10^4	299.1
0.008	8.06×10^3	833		
0.0075			9.81×10^3	730
0.0070			8.51×10^3	149.6
0.006	5.98×10^3	835	7.34×10^3	300.9
0.005			6.14×10^3	149.6
0.0045			5.35×10^3	730
0.004	4.01×10^3	833	4.86×10^3	300.9

Table V - Xe
(contd)

E/p_{300} (volts/cm-mm Hg)	W_e (195°K) (cm/sec)	p_{300} (mm-Hg)	W_e (300°K) (cm/sec)	p_{300} (mm-Hg)
0.004			4.70×10^3	149.6
0.003			3.63×10^3	149.6
0.0025			2.88×10^3	730
0.0020	2.02×10^3	571	2.51×10^3	149.6
"	$1.95 \times$ "	839	2.41×10^3	300.9
0.0015			1.84×10^3	149.6
0.0010	9.66×10^2	839	1.23×10^3	300.9
"			1.22×10^3	730
0.0005			5.78×10^2	300.9

Table VI - H_2

Drift velocity of electrons in Hydrogen
Drift distances = 1" and 2"

E/p_{300} (volts/cm-mm Hg)	W_e (77°K) (cm/sec)	p_{300} (mm-Hg)	W_e (195°K) (cm/sec)	p_{300} (mm-Hg)	W_e (300°K) (cm/sec)	p_{300} (mm-Hg)	W_e (373°K) (cm/sec)	p_{300} (mm-Hg)
10.0					4.23×10^6	4.30		
5.0					2.68×10^6	4.30		
3.0					2.0×10^6	18.44		
2.0	1.53×10^6	26.4	1.64×10^6	21.1	1.55×10^6	18.44		
"					1.51×10^6	4.30		
1.0	1.07×10^6	26.4	1.06×10^6	21.1	1.02×10^6	4.30	1.05×10^6	46.4
"			1.13×10^6	36.2	1.03×10^6	18.44		
"					1.04×10^6	53.5		
0.79			9.55×10^5	75				
0.50	8.10×10^5	26.4	8.05×10^5	21.1	7.50×10^5	18.44		
"	8.40×10^5	71.6	8.00×10^5	36.2				
"			7.94×10^5	75				
0.30			6.34×10^5	61.8				
0.25			6.0×10^5	230				
0.20	5.76×10^5	26.4	5.25×10^5	21.1	5.08×10^5	4.32	4.61×10^5	47
"	5.50×10^5	71.6	5.08×10^5	73.3	4.80×10^5	18.44	4.60×10^5	182
"	5.71×10^5	279	5.40×10^5	75	5.00×10^5	53.5		
"					4.62×10^5	203.9		
0.18	5.35×10^5	415						
0.10	3.82×10^5	26.4	3.34×10^5	29.6	3.21×10^5	18.44	2.82×10^5	46.4
"	3.78×10^5	280	3.47×10^5	73.3	3.11×10^5	52.2	3.03×10^5	182
"	3.94×10^5	415	3.67×10^5	75	3.14×10^5	201.4	2.90×10^5	591
"			3.42×10^5	230	3.00×10^5	203.9		
"			3.48×10^5	618	3.22×10^5	297		
0.08					2.85×10^5	920		
0.05	2.35×10^5	26.4	2.16×10^5	59.6	1.90×10^5	18.44	1.78×10^5	47
"	2.32×10^5	71.6	2.23×10^5	73.3	1.86×10^5	52.2	1.74×10^5	182
"	2.35×10^5	280	2.17×10^5	230	1.85×10^5	202	1.72×10^5	591
"	2.51×10^5	415	2.23×10^5	761	1.88×10^5	647		
"	2.50×10^5	916						

Table VI - H_2

(Contd)

E/p_{300} (volts/cm-mm Hg)	W_e (77°K) (cm/sec)	p_{300} (mm-Hg)	W_e (195°K) (cm/sec)	p_{300} (mm-Hg)	W_e (300°K) (cm/sec)	p_{300} (mm-Hg)	W_e (373°K) (cm/sec)	p_{300} (mm-Hg)
0.04					1.68×10^5	920		
0.03					1.27×10^5	297		
0.025			1.29×10^5	59.6	1.11×10^5	52.2	1.04×10^5	182
"			1.33×10^5	61.8	1.07×10^5	202		
0.02	1.20×10^5	71.6	1.12×10^5	73.3	8.25×10^4	204	7.7×10^4	182
"	1.25×10^5	280	1.08×10^5	230	8.75×10^4	647	8.1×10^4	591
"	1.27×10^5	415	1.10×10^5	761	9.1×10^4	927		
"	1.34×10^5	916						
0.01	7.72×10^5	280	6.0×10^4	59.6	4.55×10^4	52.2	4.04×10^4	47
"	7.80×10^5	415	6.20×10^4	73.3	4.50×10^4	202	4.10×10^4	182
"	8.10×10^5	916	5.92×10^4	230	4.92×10^4	297	3.95×10^4	591
"	7.84×10^5	1300	5.92×10^4	761	4.54×10^4	647		
0.008					3.95×10^4	920		
0.005	4.52×10^4	71.6			2.36×10^4	52.2	2.0×10^4	180
"	4.54×10^4	280	3.0×10^4	59.6	2.34×10^4	202	1.98×10^4	591
"	4.63×10^4	297	3.20×10^4	230	2.47×10^4	297		
"	4.72×10^4	916	3.10×10^4	761	2.33×10^4	647		
0.004					2.00×10^4	920		
0.00318					1.57×10^4	297		
0.003	3.06×10^4	415						
"	2.99×10^4	1290						
0.0025					1.14×10^4	201.4		
"					1.24×10^4	920		
0.002	2.08×10^4	280	1.27×10^4	230	9.8×10^3	203	8.62×10^3	181
"	2.12×10^4	916	1.28×10^4	761	1.00×10^4	297	8.50×10^3	591
"	2.10×10^4	1290			9.10×10^3	647		
"					1.00×10^4	928		
0.00124					6.06×10^3	920		
0.001	1.07×10^4	280	6.45×10^3	761	5.12×10^3	297	4.25×10^3	591
"	1.08×10^4	415			4.84×10^3	647		
"	1.08×10^4	916			5.23×10^3	920		
"	1.05×10^4	1290						

Table VI - H_2
(Contd)

E/P_{300} (volts/cm-mm Hg)	W_e (77°K) (cm/sec)	P_{300} (mm-Hg)	W_e (195°K) (cm/sec)	P_{300} (mm-Hg)	W_e (300°K) (cm/sec)	P_{300} (mm-Hg)	W_e (373°K) (cm/sec)	P_{300} (mm-Hg)
0.0008					3.94×10^3	928		
0.00075					3.82×10^3	657		
0.0005	5.02×10^3	279	3.18×10^3	761	2.57×10^3	657		
"	5.40×10^3	916			2.52×10^3	920		
"	5.14×10^3	1290						
0.0004					2.12×10^3	927		
0.000375					2.27×10^3	657		
0.0003			1.88×10^3	761				
0.00025	2.76×10^3	916						
	2.65×10^3	1290						

Table VII - D_2

Drift velocity of electrons in Deuterium
Drift distances - 2" and 4"

E/p_{300} (volt/cm-mm Hg)	W_e (77°K) (cm/sec)	p_{300} (mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)
7.45			2.90×10^6	1.74
5.45			2.44×10^6	5.08
4.46			2.18×10^6	5.09
2.98			1.73×10^6	1.74
2.68			1.62×10^6	5.09
2.23			1.47×10^6	5.09
1.49			1.19×10^6	5.09
1.19			1.06×10^6	5.09
1.00			9.56×10^5	36.1
0.89			9.06×10^5	5.09
0.81	8.61×10^5	42.3		
0.70			7.82×10^5	35.5
0.605			7.33×10^5	5.09
0.60	7.42×10^5	65.8		
0.50			6.82×10^5	36.2
0.40	6.80×10^5	65.8	6.10×10^5	100.2
0.30	6.13×10^5	66.6	5.40×10^5	35.5
0.20	5.38×10^5	66.6	4.58×10^5	35.5
0.15	4.94×10^5	65.8	4.06×10^5	100.2
0.10	4.12×10^5	393	3.19×10^5	36.2
"			2.89×10^5	100.2
0.07	3.45×10^5	393	2.36×10^5	99.3
"			2.50×10^5	99.3
0.06			2.29×10^5	100.2
"			2.19×10^5	571.2
0.0518	3.10×10^5	569		
0.050	2.94×10^5	396	2.06×10^5	288.5
0.040			1.73×10^5	100.2
0.035			1.45×10^5	656.2
0.032	2.26×10^5	916		
0.03	2.17×10^5	567	1.32×10^5	288.5
0.02	1.57×10^5	399	9.18×10^4	658.2
0.0196			9.11×10^4	100.2
0.015	1.25×10^5	914	7.11×10^4	288.5
0.01	9.21×10^4	399	4.84×10^4	100.1
0.009			4.30×10^4	658.2
0.007	6.84×10^4	569	3.35×10^4	288
0.005	4.98×10^4	543	2.42×10^4	288
0.00461			2.24×10^4	660.5
0.0035	3.68×10^4	914		
0.003			1.43×10^4	288
0.0025	2.63×10^4	543		
0.002			9.50×10^3	286.6
0.0015	1.62×10^4	914	7.25×10^3	660.5
0.001	1.02×10^4	543	4.62×10^3	286.4
0.001			5.03×10^3	286.4
0.00075	8.13×10^3	914		

Table VIII - N_2

Drift velocity of electrons in Nitrogen
Drift distances = 1" and 2" by rejection method only

E/p_{300} (volt/cm-mm Hg)	W_e (77°K) (cm/sec)	p_{300} (mm Hg)	W_e (195) (cm/sec)(all at 990 mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)	W_e (373°K) (cm/sec)(all at p_{300} = 594 mm Hg)
10.0				4.3×10^6	1.79	
3.0				1.87×10^6	1.81	
"				1.91×10^6	19.3	
1.0				8.0×10^5	19.3	
0.3				4.24×10^5	19.3	
0.2				3.9×10^5	287.1	
0.1	3.31×10^5	600		3.09×10^5	19.3	
"				3.16×10^5	287.1	
0.0945						2.95×10^5
0.08	3.40×10^5	600				
0.06			3.1×10^5			
0.05				2.73×10^5	287.1	2.52×10^5
0.04	3.70×10^5	600	2.92×10^5			
0.03			2.83×10^5			
0.02	3.52×10^5	600	2.37×10^5	1.83×10^5	287.1	1.59×10^5
0.01	2.69×10^5	600	1.52×10^5	1.08×10^5	287.1	
0.00945						8.2×10^4
0.005	1.72×10^5	600	8.36×10^4	5.80×10^4	287.1	4.70×10^4
0.002	7.51×10^4	600	3.30×10^4	5.78×10^4	531	1.95×10^4
"			3.43×10^4	2.37×10^4	287.1	
"				2.31×10^4	531	
0.0015				1.73×10^4	746	
0.001	4.06×10^4	600	1.78×10^4	1.18×10^4	287.1	9.93×10^3
"	3.82×10^4	1200		1.17×10^4	741	
"				1.21×10^4	746	
"				1.22×10^4	535.1	
0.0008				9.2×10^3	746	
0.0005	1.98×10^4	600	8.85×10^3	6.35×10^3	531	5.0×10^3
"	1.94×10^4	1200		6.35×10^3	746	3.50×10^3
0.0004	1.49×10^4	1215		5.35×10^3	746	
0.00025	1.10×10^4	600	4.54×10^3	3.22 to		
"	1.00×10^3	1200		3.82×10^3	746	
0.0002	7.94×10^3	1215				
0.00015	5.30×10^3	1200				
0.0001	4.17×10^3	1215				

Table IX - CO

Drift velocity of electrons in Carbon Monoxide
Drift distances = 2" and 4" by rejection method only

E/p_{300} (volt/cm-mm Hg)	W_e (77°K) (cm/sec)	p_{300} (mm Hg)	W_e (195°K) (cm/sec)	p_{300} (mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)
8.0					2.75×10^6	5.14
4.94					2.30×10^6	3.41
3.31					2.06×10^6	10.3
2.51					1.95×10^6	3.41
1.0					1.48×10^6	3.41
"					1.41×10^6	5.06
0.70					1.28×10^6	10.3
0.50			1.02×10^6	14.2	1.02×10^6	5.41
0.40	9.40×10^5	72.5				
0.35					8.80×10^5	10.3
0.30					8.29×10^5	31.2
0.25	7.70×10^5	72.5				
0.207			6.78×10^5	59.4		
0.20	7.65×10^5	72.5	6.91×10^5	225	6.48×10^5	31.2
0.195	7.37×10^5	135				
0.175	7.70×10^5	199				
0.150	7.76×10^5	199	6.45×10^5	225	5.55×10^5	41.0
0.125	7.81×10^5	135	6.36×10^5	225		
0.10	7.88×10^5	199	5.81×10^5	225	4.87×10^5	21.0
0.0955	7.55×10^5	166				
0.0785	6.94×10^5	511				
0.075			5.0×10^5	225	4.35×10^5	21
"					3.91×10^5	41.0
0.065	6.15×10^5	507				
0.050	5.05×10^5	139	3.67×10	225	3.40×10	21.0
0.04					2.40×10^5	16.5
0.03					1.95×10^5	21.0
0.025	2.46×10^5	135	1.95×10^5	225	1.59×10^5	20.6
0.020	2.11×10^5	507			1.30×10^5	41.0
0.015					1.17×10^5	41.0
0.0143					9.33×10^4	20.6
0.01	1.05×10^5	135	7.84×10^4	225		
"	1.02×10^5	507				
0.0075			6.12×10^4	227		
0.00503			4.06×10^4	227		
0.005	5.29×10^4	509				
0.003	3.18×10^4	509				
0.001	1.01×10^4	509				

Table X - CO_2

Drift velocity of electrons in Carbon Dioxide
Drift distances = 2" and 4" by rejection method only

E/p_{300} (volt/cm-mm Hg)	W_e (195°K) (cm/sec)	p_{300} (mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)	W_e (413°K) (cm/sec)	p_{300} (mm Hg)
7.0			7.5×10^6	2.19		
5.0			4.94×10^6	2.19		
3.0			1.83×10^6	2.19		
2.0			1.18×10^6	2.19		
"			1.15×10^6	19.75		
1.0			5.65×10^5	19.75		
0.5			2.825×10^5	19.75		
0.3			1.67×10^5	19.75		
0.2			1.17×10^5	19.75	1.07×10^5	105
0.1			5.58×10^4	19.75		
"	5.54×10^4	328	5.46×10^4	291	5.427×10^4	253
"			5.58×10^4	19.75	5.48×10^4	105
0.05	2.82×10^4	328	2.82×10^4	19.75	2.74×10^4	165
0.02	1.10×10^4	328	1.13×10^4	19.75	1.08×10^4	165
"			1.13×10^4	291	1.085×10^4	253
0.01	5.55×10^3	328	5.65×10^3	291		
0.005	2.82×10^3	328	2.825×10^3	291		
0.002	1.13×10^3	328				

Table XI - H_2O

Drift velocity of electrons in Water Vapor
Drift distances = 2" and 4" by rejection method only

E/p_{300} (volt/cm-mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)	W_e (443°K) (cm/sec)	p_{300} (mm Hg)
27.5			9.6×10^6	1.10
20	6×10^6	1.36		
18.7			5.0×10^6	1.00
18.0			3.7×10^6	.96
16.0	1.92×10^6	1.75		
15.0	1.75×10^6	1.26		
14.0	1.35×10^6	1.75	1.835×10^6	.96
13.5	1.20×10^6	2.33		
11	9.4×10^5	1.26		
10.5	9.0×10^5	1.75		
10.0	8.4×10^5	1.75	1.0×10^6	.96
8.0	6.5×10^5	1.26		
6.0			5.90×10^5	3.43
5.0			4.68×10^5	.96
4.0	3.08×10^5	2.33		
1.95	1.36×10^5	20.78		
1.50			1.37×10^5	3.43
1.00	7.40×10^4	20.3	9.40×10^4	15.2
.60			5.65×10^4	3.43
.5	3.68×10^4	20.78		
.4	3.03×10^4	2.33		
.2	1.46×10^4	5.6		
.103	7.88×10^3	5.6		
.10			9.75×10^3	15.1
.02	1.49×10^3	24.60		

Table XII - N_2O

Drift velocity of electrons in Nitrous Oxide
Drift distances = 2" and 4" by rejection method only

E/p_{300} (volt/cm-mm Hg)	W_e (195°K) (cm/sec)	p_{300} (mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)
1.50			3.69×10^6	29.5
1.33	3.63×10^6	22.11		
1.00			2.65×10^6	29.5
0.886			2.31×10^6	48.5
0.835			2.12×10^6	29.5
0.70			1.72×10^6	48.3
0.585	1.55×10^6	22.11		
0.585	1.42×11^6	50.5		
0.50			1.24×10^6	29.5
"			1.20×10^6	48.3
0.449			9.85×10^5	101.7
0.419			7.20×10^5	97.5
0.30			6.87×10^5	48.6
"			6.07×10^5	98.6
0.29	6.09×10^5	100		
0.231			5.03×10^5	97.3
0.20			4.38×10^5	29.5
"	4.24×10^5	50.5	4.27×10^5	48.1
"			3.91×10^5	101.8
0.10	2.07×10^5	50.5	2.10×10^5	48.1
"	2.06×10^5	100	1.99×10^5	97.8
"			2.00×10^5	102.2
0.07			1.48×10^5	48.2
0.0621			1.196×10^5	98.6
0.04			8.26×10^4	48.2

Table XIII - NH_3

Drift velocity of electrons in Ammonia
Drift distances = 2" and 4" by rejection method only

E/p_{300} (volt/cm-mm Hg)	W_e (195°K) (cm/sec)	p_{300} (mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)	W_e (381°K) (cm/sec)	p_{300} (mm Hg)
15.0			7.7×10^6	.71		
12.7					6.0×10^6	2.64
12.0	5.35×10^6	2.28				
10.0	2.42×10^6	2.28	2.60×10^6	.71	3.53×10^6	2.64
"	2.65×10^6	2.30	3.08×10^6	2.20	3.50×10^6	3.10
9.40			2.54×10^6	2.20		
9.0	1.91×10^6	2.28	1.95×10^6	3.75		
8.50			1.64×10^6	4.29		
8.00	1.30×10^6	2.28	1.61×10^6	2.20	1.92×10^6	3.16
7.50			1.31×10^6	.71		
7.0	1.01×10^6	2.28				
6.65			1.10×10^6	4.29	1.31×10^6	3.10
"			1.10×10^6	3.75		
6.0					1.16×10^6	3.16
5.9	7.25×10^5	6.35				
5.6	6.6×10^5	2.03				
5.0			7.5×10^5	3.75		
"			7.0×10^5	4.29		
4.0	4.38×10^5	2.03	5.6×10^5	10.62	6.95×10^5	2.64
"					6.80×10^5	3.16
3.0			4.12×10^5	13.94		
2.50	2.66×10^5	4.62	3.38×10^5	4.29		
2.0	2.18×10^5	2.03	2.82×10^5	3.75	3.39×10^5	2.64
"	2.0×10^5	17.65	2.74×10^5	13.94	3.27×10^5	3.16
"					3.23×10^5	11.2
"					3.06×10^5	14.6
1.0	1.075×10^5	2.03	1.39×10^5	3.75	1.56×10^5	11.2
"	1.00×10^5	17.65	1.37×10^5	10.62	1.59×10^5	14.6
"	9.9×10^4	41.2	1.37×10^5	13.94	1.67×10^5	3.16
"			1.35×10^5	37.7		
"			1.34×10^5	42.82		
0.50	5.32×10^4	4.62	6.74×10^4	13.94	8.06×10^4	11.2
"	4.92×10^4	64.8	6.65×10^4	85.5		
0.418			5.52×10^4	106.6		
0.400					6.30×10^4	85
.300	3.07×10^4	17.65	4.10×10^4	42.82		
.202			2.67×10^4	106.6		
.200	2.08×10^4	64.8	2.71×10^4	37.7	3.24×10^4	11.2
			2.57×10^4	175.5	3.23×10^4	14.6
.171			2.26×10^4	85.4		
.100	1.025×10^4	64.8	1.35×10^4	42.82	1.58×10^4	11.2
			1.32×10^4	106.6		
.0945			1.21×10^4	175.5		
.089	9.70×10^3	57.6				
.052	5.60×10^3	41.2				
.05	5.20×10^3	64.8	6.85×10^3	37.7		
"			6.86×10^3	175.5		
.04					6.12×10^3	85.0

Table XIII - NH_3

(Contd)

E/p_{300} (volt/cm-mm Hg)	W_e (195°K) (cm/sec)	p_{300} (mm Hg)	W_e (300°K) (cm/sec)	p_{300} (mm Hg)	W_e (381°K) (cm/sec)	p_{300} (mm Hg)
.0343	3.65×10^3	51.6				
.0300			4.03×10^3	37.7		
			4.06×10^3	42.82		
.02	2.08×10^3	64.8			3.30×10^3	85.0
.01			1.37×10^3	120.9		

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY *(Corporate author)* Westinghouse Research Laboratories	2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED 2b. GROUP

3. REPORT TITLE

TABLES OF DRIFT VELOCITIES OF SLOW ELECTRONS IN HELIUM, NEON, ARGON, KRYPTON, XENON, HYDROGEN, DEUTERIUM, NITROGEN, CARBON MONOXIDE, CARBON DIOXIDE, WATER VAPOR, NITROUS OXIDE, AND AMMONIA

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*

Technical Report

5. AUTHOR(S) *(Last name, first name, initial)*

Pack, J. L.
Voshall, R. E.
Phelps, A. V.

6. REPORT DATE July 23, 1962	7a. TOTAL NO. OF PAGES 21	7b. NO. OF REFS 2

8a. CONTRACT OR GRANT NO. NONR-2584(00) b. PROJECT NO. 7200 c. ARPA Order No. 125-61 (Amd. 4) d.	9a. ORIGINATOR'S REPORT NUMBER(S) Research Report 62-928-113-R1 9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)* Technical Report #13

10. AVAILABILITY/LIMITATION NOTICES

Distribution of this document is unlimited

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Advanced Research Projects Agency through Office of Naval Research

13. ABSTRACT

This report presents in tabulated form the drift velocities of electrons in various gases. The drift velocities were measured in helium, neon, argon, krypton, xenon, hydrogen, deuterium, nitrogen, carbon monoxide, carbon dioxide, water vapor, nitrous oxide, and ammonia for E/p values from 10^{-4} to 30 volts/cm-mm Hg at several gas temperatures between 77°K and 443°K. In all gases except neon measurements were extended to low enough E/p such that the electrons were in thermal equilibrium with the gas.

DD FORM 1 JAN 64 1473

UNCLASSIFIED

Security Classification

RM 35054

14 KEY WORDS	LINK A ROLE	LINK A WT	LINK B ROLE	LINK B WT	LINK C ROLE	LINK C WT
Electron						
Drift Velocity						
Experiment						
Helium						
Neon						
Argon						
Krypton						
Xenon						
Hydrogen						
Deuterium						
Nitrogen						
Carbon Monoxide						
Carbon Dioxide						
Water Vapor						
Nitrous Oxide						
Ammonia						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS)*, *(S)*, *(C)*, or *(U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

RM 35055